



Technical Data



TECHNICAL DATA

| | |
|---------------------|--|
| Matchcode | RSV-210-XL-SFS |
| Article name | Smoke curtain system Smoke PROtec RSV-210-XL-SFS |
| Part number | RSV 52041 |
| Classification | EN 12101-1, ASB 3, D120 (fail-safe) 120 minutes at 600 Å°C |
| Fabric | One-side PU-coated glass fabric 590 g/m2, colour: grey, non-inflammable according to DIN 4102-1, A2, smoke-proof tested according to the test procedures in accordance with DIN EN 1634-3. |
| Unwind | descending by gravity (gravity fail safe) |
| Rewind | planet drive, 24 V DC, 3 A with electric load breaking; maximum turning moment 4 Nm, roll shaft-integrated. |
| System installation | Ceiling or wall mounted with appropriate approved mounting material |
| System size | max 6 x 6 m (WxH) |
| Housing | Galvanized sheet steel 1 mm powder-coated RAL 7035; Single roller 180 x 210 mm; Side guides: Sheet steel 1.5 mm powder-coated RAL 7035, 50 x 100 mm (WxD) |
| Bottom Bar | Sheet steel 1 mm powder-coated RAL 7035 with integrated round steel in fabric bag for energy free dropping |
| Housing type | Steel case |
| Colour | RAL 7035 |

ACCESSORIES

| Part no. | Matchcode | |
|--------------------------|-----------------------------------|--|
| A3 2064 | RM 3000 FSV | |
| A3 2178 | HE 087 Yellow FSV | |
| M2 3330 | AM-830 | |
| ST4 3170 | SHEV 3 RSV | |
| ST4 3171 | SHEV 6 RSV | |
| ST4 3422 | M-SHEV-24-RSV | |

[ST4 3423](#)

[M-SHEV-12-RSV](#)