FIRE PROtec EI 120 MARC

version 2022/A

SIMON
we create fire safety

CLEAR OPENING HEIGHT Hu [mm]	601 - 1 000	1 001 - 1 500	1 501 - 2 000	2 001 - 2 500	2 501 - 3 000	3 001 - 3 500	3 501 - 4 000	4 001 - 4 500	4 501 - 5 000	5 001 - 5 500	5 501 - 6 000	6 001 - 6 500	6 501 - 7 000	7 001 - 7 500	7 501 - 8 000	8 001 - 8 500	8 501 - 9 000	9 001 - 9 500	9 501 - 10 000	10 001 - 10 500	10 501 - 11 000	11 001 - 11 500	11 501 - 12 000
9751 - 10 000	3	3	5	5	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7	7
9 501 - 9 750	3	3	5	5	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7	7
9 251 - 9 500	3	3	5	5	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7	7
9 001 - 9 250	2	3	5	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7
8 751 - 9 000	2	3	5	5	6	6	6	6	6	5	7	7	7	7	7	7	7	7	7	7	7	7	7
8 851 - 8 750	2	3	5	5	6	6	6	6	6	5	7	7	7	7	7	7	7	7	7	7	7	7	7
8 251 - 8 500	2	3	5	5	5	6	6	6	6	5	7	7	7	7	7	7	7	7	7	7	7	7	7
8 001 - 8 250	2	3	5	5	5	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7
7 751 - 8 000	2	3	3	5	4	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7	7
7 501 - 7 750	2	3	3	5	4	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7
7 251 - 7 500	2	3	3	5	4	5	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7	7
7 001 - 7 250	2	3	3	5	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7
6 751 - 7 000	2	3	3	5	5	4	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7	7
6 501 - 6 750	2	2	3	3	5	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7
6 251 - 6 500	2	2	3	3	5	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7	7
6 001 - 6 250	2	2	3	3	5	4	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7
5 751 - 6 000	2	2	3	3	3	4	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7	7
5 501 - 5 750	2	2	3	3	3	4	4	4	5	6	6	6	6	6	6	7	7	7	7	7	7	7	7
5 251 - 5 500	1	2	2	3	3	4	4	4	5	6	6	6	6	6	6	6	7	7	7	7	7	7	7
5 001 - 5 250	1	2	2	3	3	4	4	4	4	5	6	6	6	6	6	6	6	7	7	7	7	7	7
4 751 - 5 000	1	2	2	3	3	3	4	4	4	5	6	6	6	6	6	6	6	6	7	7	7	7	7
4 501 - 4 750	1	2	2	3	3	3	4	4	4	5	5	6	6	6	6	6	6	6	7	7	7	7	7
4 251 - 4 500	1	2	2	2	3	3	3	4	4	4	5	6	6	6	6	6	6	6	7	7	7	7	7
4 001 - 4 250	1	2	2	2	3	3	3	5	4	4	4	6	6	6	6	6	6	6	6	7	7	7	7
3 751 - 4 000	1	1	2	2	2	3	3	3	4	4	4	4	6	6	6	6	6	6	6	7	7	7	7
3 501 - 3 750	1	1	2	2	2	3	3	3	4	4	4	4	6	6	6	6	6	6	6	7	7	7	7
3 251 - 3 500	1	1	2	2	2	2	3	3	3	4	4	4	4	6	6	6	6	6	6	7	7	7	7
3 001 - 3 250	1	1	2	2	2	2	3	3	3	4	4	4	4	6	6	6	6	6	6	6	7	7	7
2 751 - 3 000	1	1	1	2	2	2	3	3	3	3	4	4	4	6	6	6	6	6	6	6	6	7	7
2 501 - 2 750	1	1	1	2	2	2	2	3	3	3	3	4	4	5	6	5	6	6	6	6	6	6	6
2 251 - 2 500	1	1	1	1	2	2	2	2	3	3	3	3	4	4	4	6	6	6	6	6	6	6	6
2 001 - 2 250	1	1	1	1	2	2	2	2	2	3	3	3	3	4	5	5	5	6	6	6	6	6	6
1 751 - 2 000	1	1	1	1	1	2	2	2	2	2	3	2	3	4	4	5	5	5	6	6	6	6	6
1 501 - 1 750	1	1	1	1	1	1	2	2	2	2	3	3	3	4	4	4	4	5	5	6	6	6	6
1 251 - 1 500	1	1	1	1	1	1	1	2	2	2	2	3	3	4	4	4	4	4	4	6	5	6	6
1 001 - 1 250	1	1	1	1	1	1	1	2	2	2	2	2	2	3	4	4	4	4	4	4	4	4	6
100 - 1 000	1	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3	3	4	4	4	4	4	4

CLEAR OPENING WIDTH Su [mm]

DIAGRAM LEGEND

HOUSING DIMENSIONS Sk x Hk [mm]

- 775 x 800
- 725 x 750
- 675 x 700
- 625 x 650
- 575 x 600
- 525 x 550
- 475 x 500
- 425 x 450
- 375 x 400
- 325 x 350

DRIVE TYPE

1. VIC-0122 [Gr230/24/2]
2. VIC-0123 [Gr230/24/2]
3. VIC-0124 [Gr230/24/2]
4. VIC-0461 [Gr230/24/4]
5. VIC-0242 [ZGr400/2]
6. VIC-0243 [ZGr400/3]
7. VIC-0244 [ZGr400/5]

MARKING OF DRIVES

- ☐ - power supply before the main switch (guaranteed) necessary to close the gate
- Z - external drive
- P - fire resistant cables must be coneccted to the connection
- Gr - gravity operated drive
- 230 - the value of the voltage applied to the control panel [V]
- /4 - minimum connection value [A]

Wall mounting (with the internal drive)



Cross corridor mounting (with the internal drive)



All dimensions are in millimeters [mm]

Notations used in the drawings:

- So - structural / wall opening width
- Su - clear opening width
- Ho - structural / wall opening height
- Hu - clear opening height
- Sk - housing width
- Hk - housing height

NOTICE

In the case of the cross corridor mounting, there should be an installation clearance of 10 mm per side.