Folding Arm² Turning actuator EA-KL²-DF-K-C



Technical Data

Input voltage	24 V DC
Nominal current	1.1
Opening angle	140
IP code	IP54
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA-KL²-DF-K-C
Article name	Folding Arm² Turning actuator EA-KL²-DF-K-C
Part number	M2 1496 C
Input voltage	24 V DC
Nominal current	1.1
Input voltage range	- 15 % / + 15 %
Ripple	500
Opening angle	140
Push force	400
Pull force	400
Nominal locking force	700
Cut-Off	Integrated electronic overload cut-off
Running speed	3.1
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	3.60
Housing	Aluminium profile housing E6 / EV1 anodized
Housing type	Aluminium
Colour	RAL & DB colors
Housing length	368
Housing width	58
Housing height	118
Appliance class	III
Connection cable	Silicone cable 6 x 0.75 mm², light gray, length 3,000 mm
Nominal working temperature	20
Environment temperature range	0 °C - 75 °C
Brackets included	nein

ACCESSORIES

Part no.	Matchcode	
K2 1695	K-KL²-DF-800	
K2 1696	K-KL²-DF-600	
K2 1697	K-KL²-DF-400	
SD1 8530	Software parameterization	