
Folding Arm² EA-KL²-L-C



Technical Data

Input voltage	24 V DC
Nominal current	3
Running speed	23
IP code	IP54
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA-KL²-L-C
Article name	Folding Arm² EA-KL²-L-C
Part number	M2 1517 C
Input voltage	24 V DC
Nominal current	3
Input voltage range	- 15 % / + 25 %
Stroke	1200
Push force	550
Pull force	550
Nominal locking force	660
Cut-Off	Integrated overload cut-off with microprocessor
Running speed	23
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	7.6
Housing	Aluminum
Housing type	Aluminium
Colour	Alu EV6/EV1
Housing length	751
Housing width	58
Housing height	165
Appliance class	III
Connection cable	Silicone cable 6 x 0.75 mm², light gray, length 2,000 mm
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C

Folding Arm² EA-KL²-L-C

ACCESSORIES

Part no.	Matchcode	
K2 1608	K-KL²-M-OK	
K2 1609	K-KL²-S-OK	
K2 1617	Z-K-KL-DP25	
K2 1623	K-KL²-M(S)-RAICO100/120RI	
K2 1624	K-KL²-WICONA-LI	
K2 1625	K-KL²-WICONA-RE	
K2 1647	K-KL²-L-WICONA-LI	
K2 1648	K-KL²-L-WICONA-RE	
K2 1649	K-KL²-L-RAICO105D-LI	
K2 1650	K-KL²-L-RAICO105D-RE	
K2 1651	K-KL²-L-LK-LI	
K2 1652	K-KL²-L-LK-RE	
K2 1653	K-KL²-L-AWS57RO-LI	
K2 1654	K-KL²-L-AWS57RO-RE	
K2 1680	Z-K-KL2-DP5	
K2 1681	Z-K-KL2-DP10	
K2 1682	Z-K-KL2-DP17	
K2 1683	Z-K-KL2-DP22	
SD1 8530	Software parameterization	