



Technical Data



| | |
|----------------|----------|
| Input voltage | 230 V AC |
| Output voltage | 24 V DC |
| Output current | 72 |

TECHNICAL DATA

| | |
|-------------------------------|--|
| Matchcode | M-SHEV-72 |
| Article name | modul control panel M-SHEV-72 |
| Part number | ST4 3451 |
| Input voltage | 230 V AC |
| Output voltage | 24 V DC |
| Output current | 72 |
| Classification | CE certified EN 12101-10, tested ISO 21927-9 |
| LED signs | LED display operating status network: Permanent display green - mains available LED display operating status lead acid battery ("O.K."): Continuous green - battery is present and charging (charge is being maintained) |
| IP code | IP66 |
| Housing | Sheet steel case |
| Housing type | Steel case |
| Colour | RAL7035 |
| Housing width | 800 |
| Housing height | 800 |
| Housing depth | 250 |
| Appliance class | I |
| Environment temperature range | -5°C - +40°C |

ACCESSORIES

| Part no. | Matchcode |
|---------------------------|--|
| ST4 10120 | Pb-battery-7Ah |
| ST4 10121 | pb-battery-12ah |
| ST4 10122 | pb-battery-17ah |
| ST4 10123 | pb-battery-24ah |
| ST4 10124 | Pb battery 38 Ah |
| ST4 3321 | Flange plate 445-130 plastic |
| ST4 3322 | Flange plate 345-130 plastic |
| ST4 3323 | Flange plate 545-130 plastic |
| ST4 3344 | HR-820-MS |

| | |
|--------------------------|-------------------------------|
| ST4 3380 | ZI-100 |
| ST4 3381 | SI-100 |
| ST4 3382 | MI-100 |
| ST4 3383 | MR-120 |
| ST4 3385 | MI-100-MB |
| ST4 3386 | SI-100-MASTER |
| ST4 3389 | BI-100-KNX |