

## **Ventilation control unit M-VENT-5-S**



#### **Technical Data**



Input voltage 230 V AC
Output voltage 24 V DC

Output current 5

### **TECHNICAL DATA**

Matchcode M-VENT-5-S

Article name Ventilation control unit M-VENT-5-S

Part number ST4 4043
Input voltage 230 V AC
Output voltage 24 V DC

Output current

LED signs white: WTS; yellow: failure; green: OK

IP code IP66 Weight 11.5

Housing Sheet steel housing 400 x 600 x 200 mm

(WxHxD), integrated mounting

Housing typeSteel caseColourRAL 7035Housing width400Housing height600Housing depth200

Environment temperature range -5°C - +60°C

#### **ACCESSORIES**

Part no.	Matchcode
ST4 10120	Pb-battery-7Ah
ST4 10121	pb-battery-12ah
ST4 10122	pb-battery-17ah
ST4 10123	pb-battery-24ah
ST4 10124	Pb battery 38 Ah
ST4 3321	Flange plate 445-130 plastic
ST4 3322	Flange plate 345-130 plastic
ST4 3323	Flange plate 545-130 plastic
ST4 3344	HR-820-MS
ST4 3361	Charge electronics, type LB-120
ST4 3362	Charge electronics, type LB-140
ST4 3363	Charge electronics, type LB-160



# **Ventilation control unit M-VENT-5-S**

ST4 3369	Charge electronics, type LB-120-10
ST4 3380	ZI-100
ST4 3381	<u>SI-100</u>
ST4 3382	<u>MI-100</u>
ST4 3383	MR-120
ST4 3385	<u>MI-100-MB</u>
ST4 3386	SI-100-MASTER
ST4 3389	BI-100-KNX