



Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	24

TECHNICAL DATA

Matchcode	M-SHEV-24/1-2-ECO
Article name	Modular control panel M-SHEV-24 /1-2-ECO
Part number	ST4 3439
Input voltage	230 V AC
Output voltage	24 V DC
Output current	24
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LEDs on the loading card: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules
IP code	IP66
Housing	Sheet steel case
Housing type	Steel case
Colour	RAL 7035
Housing width	500
Housing height	500
Housing depth	200
Appliance class	I
Environment temperature range	-5°C - +40°C

ACCESSORIES

Part no.	Matchcode	
ST4 10120	Pb-battery-7Ah	
ST4 10121	pb-battery-12ah	
ST4 10122	pb-battery-17ah	
ST4 10123	pb-battery-24ah	
ST4 10124	Pb battery 38 Ah	
ST4 3321	Flange plate 445-130 plastic	
ST4 3322	Flange plate 345-130 plastic	
ST4 3323	Flange plate 545-130 plastic	
ST4 3344	HR-820-MS	
ST4 3361	Charge electronics, type LB-120	

<u>ST4 3362</u>	<u>Charge electronics, type LB-140</u>
<u>ST4 3363</u>	<u>Charge electronics, type LB-160</u>
<u>ST4 3369</u>	<u>Charge electronics, type LB-120-10</u>
<u>ST4 3380</u>	<u>ZI-100</u>
<u>ST4 3381</u>	<u>SI-100</u>
<u>ST4 3382</u>	<u>MI-100</u>
<u>ST4 3383</u>	<u>MR-120</u>
<u>ST4 3385</u>	<u>MI-100-MB</u>
<u>ST4 3386</u>	<u>SI-100-MASTER</u>