# Modular control panel M-SHEV-12-RSV



## Technical Data

SIMON LINK

## TECHNICAL DATA

| | |
|---|---|
| Matchcode | M-SHEV-12-RSV |
| Article name | Modular control panel M-SHEV-12-RSV |
| Part number | ST4 3423 |
| Input voltage | 230 V AC |
| Output voltage | 24 V DC |
| Output current | 12 |
| LED signs | LEDs on the loading card: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules |
| IP code | IP54 |
| Mounting way | aufgesetzt |
| Housing | steel case housing 400 x 600 x 200 mm |
| Housing type | Steel case |
| Colour | RAL 7035 light grey |
| Housing length | 400 |
| Housing width | 600 |
| Housing height | 250 |
| Appliance class | I |
| Environment temperature range | -5 °C bis 40 °C |

## ACCESSORIES

| Part no. | Matchcode | |
|---|---|---|
| ST4 10120 | Pb-battery-7Ah | |
| ST4 10121 | pb-battery-12ah | |
| ST4 10122 | pb-battery-17ah | |
| ST4 10123 | pb-battery-24ah | |
| ST4 10124 | Pb battery 38 Ah | |
| ST4 3321 | Flange plate 445-130 plastic | |
| ST4 3322 | Flange plate 345-130 plastic | |
| ST4 3323 | Flange plate 545-130 plastic | |
| ST4 3380 | ZI-100 | |
| ST4 3381 | SI-100 | |

| | |
|---|---|
| ST4 3382 | MI-100 |
| ST4 3383 | MR-120 |
| ST4 3386 | SI-100-MASTER |