



Technical Data



| | |
|--------------------|---------|
| Input voltage | 24 V DC |
| Nominal current | 1.3 |
| Opening angle | 122 |
| IP code | IP54 |
| Switch on duration | 30 |

MOUNTING POSITIONS



TECHNICAL DATA

| | |
|-------------------------------|-----------------------------------------------------------------|
| Matchcode | PA-KL ² -T-K-50/122deg |
| Article name | Folding Arm ² door opener PA-KL ² -T-K-50 |
| Part number | M2 2023 |
| Input voltage | 24 V DC |
| Nominal current | 1.3 |
| Input voltage range | - 15 % / + 15 % |
| Ripple | 500 |
| Networked standby | 0.9 W (1 min) |
| Opening angle | 122 |
| Push force | 500 |
| Pull force | 50 |
| Classification | EN 12101-2, EN 60335-1, EN 60335-2-103 |
| Cut-Off | Integrated overload cut-off with microprocessor |
| Running speed | 2 |
| IP code | IP54 |
| Switch on duration | 30 |
| Weight | 3.7 |
| Housing | Aluminium housing E6 / EV1 anodized |
| Housing type | Aluminium |
| Colour | RAL & DB colors |
| Housing length | 382 |
| Housing width | 58 |
| Housing height | 118 |
| Appliance class | III |
| Connection cable | SICO PLUG connection. Excluding connection cable / set. |
| Nominal working temperature | 20 |
| Environment temperature range | 0 °C - 75 °C |
| Brackets included | nein |

ACCESSORIES

| Part no. | Matchcode | |
|--------------------------|-------------------------------------------------|--|
| K2 1620 | K-KL²-T-MW | |
| K2 1621 | K-KL²-T-MP | |
| K2 2001 | SICO-PLUG | |
| K2 2002 | SICO-PLUG-SP | |
| K2 2003 | PA-ANL-SIHF-6x0.5mm² | |
| K2 2004 | PA-ANL-3m | |
| K2 2005 | PA-ANL-5m | |
| K2 2006 | PA-ANL-+lfm | |
| K2 2007 | PA-SICO-SET-3m | |
| K2 2008 | PA-SICO-SET-5m | |
| K2 2009 | PA-SICO-SET-+lfm | |
| SD1 8513 | SICO-LINK-USB-110 | |
| SD1 8514 | SICO-PLUG-INSTALL | |
| SD1 8522 | SICO-LINK-Adapter | |
| SD1 8525 | SICO-PLUCKER | |
| SD1 8530 | Software parameterization | |