

Linear actuator PA-L-75/1000-S

Technical Data













Input voltage 24 V DC

Nominal current 1.1
Running speed 7.6
IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode
Article name
Part number
Input voltage
Nominal current
Input voltage range
Networked standby

Stroke Push force Pull force

Nominal locking force

Cut-Off

Running speed

IP code

Switch on duration Mounting way

Weight Housing

Housing type

Colour Housing length Housing height Diameter Appliance class

Connection cable

PA-L-75/1000-S

Linear actuator PA-L-75/1000-S

M2 2415 S 24 V DC

1.1

- 15 % / + 15 % 0.9 W (1 min)

Integrated electronic overload cut-off

7.6 IP54 30

aufgesetzt

3.55

End-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

bracket system
Aluminium
On request

1387 42 36

SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-75/1000-S

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
K2 1502	DAS
<u>K2 1505 A</u>	<u>UKU-740</u>
K2 1506	<u>AW 100-6</u>
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	<u>AW 150-6</u>
K2 1507 B	<u>AW 150-6-A</u>
K2 1519 A	AW 250-6
K2 1539	<u>HK-L</u>
K2 1562	<u>UK-L</u>
<u>K2 1563</u>	K-L-UK-J
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
K2 1577	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
<u>K2 2005</u>	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+Ifm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER