

## Linear actuator PA-L-100/120-S

### **Technical Data**













Input voltage 24 V DC

Nominal current 1.0
Running speed 4.4
IP code IP54

Switch on duration 30

#### **MOUNTING POSITIONS**

























#### **TECHNICAL DATA**

Matchcode PA-L-100/120-S Article name Linear actuator PA-L-100/120-S

Part number M2 2426 S
Input voltage 24 V DC
Nominal current 1.0
Input voltage range - 15 % / + 15 %

Networked standby

Stroke

Push force

Dull force

1000

Pull force 1000 Nominal locking force 1000

Cut-Off integrated electronic overload cut-off

Running speed 4.4
IP code IP54
Switch on duration 30

Switch on duration 30 Mounting way aufgesetzt

Weight 1.3

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 507
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



# Linear actuator PA-L-100/120-S

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	OK
K2 1502	DAS
<u>K2 1505 A</u>	<u>UKU-740</u>
K2 1506	AW 100-6
K2 1506 A	AW 100-6-A
K2 1507 A	AW 150-6
<u>K2 1507 B</u>	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	<u>HK-L</u>
<u>K2 1562</u>	<u>UK-L</u>
<u>K2 1563</u>	K-L-UK-J
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+Ifm
K2 2007	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER