

Linear actuator PA-L-90/500

Technical Data











Input voltage 24 V DC

Nominal current 1.2
Running speed 7.6
IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-90/500
Article name Linear actuator PA-L-90/500

Part number M2 2433 Input voltage 24 V DC Nominal current 1.2

Input voltage range -15%/+15%Networked standby 0.9% (1 min) Stroke 500

Stroke500Push force900Pull force900Nominal locking force1000

Cut-Off integrated electronic overload cut-off

Running speed 7.6
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 2.2

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 887
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-90/500

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES		
	Matcheodo	
Part no.	Matchcode	
<u>K2 1501</u>	<u>OK</u>	
<u>K2 1502</u>	DAS	
K2 1505 A	<u>UKU-740</u>	
K2 1506	AW 100-6	
K2 1506 A	AW 100-6-A	
K2 1507 A	<u>AW 150-6</u>	
K2 1507 B	AW 150-6-A	
K2 1519 A	AW 250-6	
<u>K2 1539</u>	<u>HK-L</u>	
<u>K2 1562</u>	<u>UK-L</u>	
K2 1563	<u>K-L-UK-J</u>	
<u>K2 2004</u>	PA-ANL-3m	
<u>K2 2005</u>	PA-ANL-5m	
<u>K2 2006</u>	PA-ANL-+lfm	
K2 2007	PA-SICO-SET-3m	
<u>K2 2008</u>	PA-SICO-SET-5m	
<u>K2 2009</u>	PA-SICO-SET-+lfm	
SD1 8522	SICO-LINK-Adapter	
SD1 8525	SICO-PLUCKER	